

3 and a transparent coating film 7 which is formed on the transparent electrodes 9. The electrophoresis of the electrifiable particulates 4 to, for example, the transparent electrode 9 side is effected in the hot meltable material 3 melted by impressing voltage to the electrodes 2, 9 by which the hue occurring in the electrifiable particulates 4 is displayed from the transparent electrode 9 side. The electrophoresis to the counter electrode 2 side is effected, by which the hue occurring in the hot meltable material 3 is displayed from the transparent electrode 9 side.

LEGAL STATUS

- [Date of request for examination]
- [Date of sending the examiner's decision of rejection]
- [Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]
- [Date of final disposal for application]
- [Patent number]
- [Date of registration]
- [Number of appeal against examiner's decision of rejection]
- [Date of requesting appeal against examiner's decision of rejection]
- [Date of extinction of right]

Copyright (C): 1998 Japanese Patent Office

MENU SEARCH INDEX BACK NEXT

B212

MENU SEARCH INDEX BACK NEXT

1536



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11)Publication number: 08006508
(43)Date of publication of application: 12.01.1996

(51)Int.Cl. G09F 9/37

(21)Application number: 07092278 (71)Applicant: TOSHIBA CORP
(22)Date of filing: 18.04.1995 (72)Inventor: TAKAYAMA AKIRA
SUGIUCHI MASAMI

(56)Priority

Priority number: 06 84461 Priority date: 22.04.1994 Priority country: JP

(54) DISPLAY MEDIUM AND ITS DISPLAY METHOD

(57)Abstract:

PURPOSE: To make it possible to hold images even if the number of repetitive use times is large and there is no supply of energy by providing a display medium with a container of which at least one surface consist of a transparent material and a specific image forming medium. CONSTITUTION: This display medium is composed of the container which includes transparent electrodes 9 and a counter electrode 2 formed on a supporting base body 1, the image forming medium 5 which is arranged between the respective electrodes 2 and 9 and consists of columnar materials 6 for separating the container to respective cells, an insulating hot meltable material 3 separated by these columnar materials 6 and electrifiable particulates 4 as migration particles dispersed in these hot meltable material

